

---

## BUNGALOW

---

The second most common architectural style in Canemah is the Bungalow, built between 1909-1928 in the later portion of the historic period. While many of the homes in this style are located on the river side of McLoughlin Boulevard, others are scattered on the hillside up to 4<sup>th</sup> Street, but generally on more level lots. Use of this style south of 3<sup>rd</sup> Street requires analysis of adjacent context houses to ensure necessary variety. Important style characteristics as found on houses in the Canemah District to be used for new construction are noted below.



Built: 1920

## CHARACTERISTICS OF THE STYLE

### Site

- No uniform front setback; South of 3<sup>rd</sup> Street: houses may face front or side depending on topography, and may be irregularly situated.
- Lots range from 50x100 to 100x100 and contain a single house.
- Properties edges often not defined; Where fenced, primarily low slat or picket at front with side or partial returns.
- Planting: South of 3<sup>rd</sup> Street: forest setting, native and ornamental plantings form visual screen and sense of privacy; Elsewhere, lawn, and planted area around buildings.
- House Placement: to suit the existing topography and most level lot portion especially south of 3<sup>rd</sup> Street
- Retaining walls: stone, mortared or stacked basalt, or concrete south of 3<sup>rd</sup> Street, especially in proximity with street.
- Garages: Not found historically; informal graveled parking next to street or along house; New garages to be located along side or behind house. Where topography is a concern, locate garage offset from building primary façade, close to street with direct access.
- Accessory Buildings: detached, along side or behind house and located to allow use of particular function.
- Streets: South of 3<sup>rd</sup> Street: narrow, without curbs or sidewalks; casual pedestrian paths and connecting stairs are encouraged.

## Building Form

- Building form is difficult to modify for additions, but has versatile floor plan.
- More emphasis on the horizontal than Vernacular; this extends into porch, dormer and window design; more 'ground hugging'.
- Shape: floor plans are either rectangular, or square
- Height: One, or more often one-and-a-half stories high; possible basement.
- Proportions: Height to width approximately 1:1½; Height to Depth: 1: no more than 2 for main building portion not including front porch.
- Roof: Low-pitched (6:12 minimum) gable roof; front or side facing.
- Bays: possible single story, cantilevered, and rectangular located on side of house.
- Porch: Prominent front porch, roof supported with simple posts (less bulky than in McLoughlin); roof often continues down to create cover over porch; at main story only.



Built: 1916



Built: 1913

## Design Composition

- Front façade can be symmetrical or asymmetrical
- Porch: full, not typically wrap-around front porches.
- Roof Overhang: wide, over-hanging eaves and exposed rafter tails; decorative knee brackets under eaves.
- Dormers: single front facing; with lower slope gable or shed roofs
- Chimneys: at interior or projecting on side of house, usually brick.
- Siding: horizontal board siding; typically bevel profile (occasionally shiplap), shingle siding; or a combination, such as horizontal boards on the first floor with shingles on the second floor, or just in the gable or dormer.
- Windows: double-hung; 1:1; large fixed window flanked by two smaller double-hung windows.
- Windows At Dormers: smaller, often grouped at shed dormers; fixed or casement style where smaller.
- Finishes: generally earth tones; no white doors or windows.