

---

## RESIDENTIAL BUILDING STYLES

### VERNACULAR

---

In the Canemah Neighborhood the most prevalent extant architectural style is Vernacular, built between 1867-1929. Important style characteristics as found on houses in the Canemah District to be used for new construction are noted below.



Built: 1867

### CHARACTERISTICS OF THE STYLE

#### Site

- No uniform front setback; South of 3<sup>rd</sup> Street: houses may face front or side depending on topography.
- Lots range from 50x100 to 100x100 and contain a single house.
- Properties edges often not defined; Where fenced, primarily picket or low slat at front with side or partial returns.
- Planting: South of 3<sup>rd</sup> Street: forest setting, native and ornamental plantings form visual screen and sense of privacy; Elsewhere on the more level portions: lawn and planted area around buildings.
- House Placement: to suit the existing topography and most level lot portion especially south of 3<sup>rd</sup> Street.
- Retaining walls: stone, mortared or stacked basalt, or concrete south of 3<sup>rd</sup> Street, especially in proximity with street.
- Garages: Not found historically; informal graveled or paved parking next to street or along house; New garages to be located along side or behind house. Where topography is a concern, locate garage offset from building primary façade, close to street with direct access.
- Accessory Buildings: detached, behind along side of house and located to allow use of particular function.
- Streets: South of 3<sup>rd</sup> Street: narrow, without curbs or sidewalks; casual pedestrian paths and connecting stairs are encouraged.

## Building Form

- Form easily allows additions and alterations such as increases in family size, activities or changing technology; generally smaller in size than McLoughlin.
- Shape: rectangular in plan, with smaller rectangular combinations to primary form; Rectangular or square form reinforced on façade. L-plan, T-plan options.
- Height: Maximum 1 ½ stories in height; Basement option.
- Proportions: Height (eave) to maximum width: 1:1 Height to Depth: can vary greatly.
- Roof: gable, of not less than 8:12 pitch, 10:12 and steeper are preferred. No cross-gable roofs; Possible wing or addition with lower ridgeline that is perpendicular or is offset.



Built: 1875



Built: 1864

## Design Composition

- Lacks rigid system of exterior detailing that makes it a clearly definable architectural style; allows design flexibility and is inherently varied.
- Designed and built without assistance of a trained architect. Collaborative design evolved with homeowner and builder, based on familiar styles, features and products.
- Can combine features from other architectural styles popular during the historic period; simpler designs than McLoughlin.
- Porch: full or partial length at the front entry; if close to the ground, no railings; at main story only.
- Dormers: None.
- Materials: local, readily available.
- Windows: 1:1, double hung windows.
- Siding: horizontal board siding; typically shiplap, or channel; occasionally bevel.
- Ornament: Exterior decoration is modest, consisting of scroll-work brackets at the top of porch pillars, plain cornerboards and simple window trim. Most houses do not feature spindlework in the peaks of their gable roofs.
- Interior fireplaces and chimneys.



Built: 1885